



SCHEDULE

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Light Loss Factor	Wattage
	SL	1	Lithonia Lighting	DSXO LED P2 30K LCCO VOLTAGE MOUNTING XX FINISH	DSXO LED P2 30K LCCO VOLTAGE MOUNTING XX	0.9	49
	WP	4	Lithonia Lighting	WEDGE LED P1 30K 80CRI VW VOLTAGE MOUNTING XX FINISH	WEDGE LED WITH P1 - PERFORMANCE PACKAGE 3000K 80CRI VISUAL COMFORT WIDE OPTIC	0.9	10,000

STATISTICS

DESCRIPTION	SYMBOL	AVG.	MAX	MIN.	MAX/MIN	AVG/MIN
Boundary	+	0.2 fc	8.4 fc	0.0 fc	N/A	N/A
Pavement	X	0.9 fc	6.8 fc	0.0 fc	N/A	N/A

NOTES:

- REFLECTANCES ASSUMED: GROUND: 20
- MOUNTING HEIGHTS: SL: 12'-0" AFG, WP: 15'-0" AFG.
- TASK HEIGHT: AFG.
- CALCULATION POINT SPACING: 4 X 4 OC

DISCLAIMER:
THESE DRAWINGS ARE FOR CONCEPTUAL PURPOSES ONLY AND ARE NOT INTENDED FOR CONSTRUCTION. VALUES REPRESENTED ARE AN APPROXIMATION GENERATED FROM MANUFACTURERS PHOTOMETRIC IN-HOUSE OR MANUFACTURER'S TEST WITH DATA SUPPLIED BY LAMP MANUFACTURERS.

Note
Decorative fixtures/symbols are not shown for clarity and will not effect the footcandle levels appreciably

Plan View
Scale - 1" = 6ft